

(19)



Europäisches Patentamt

European Patent Office

Office européen des brevets



(11)

EP 0 930 136 A2

(12)

## EUROPEAN PATENT APPLICATION

(43) Date of publication:

21.07.1999 Bulletin 1999/29

(51) Int. Cl.<sup>6</sup>: B25J 15/00

(21) Application number: 98309247.9

(22) Date of filing: 11.11.1998

(84) Designated Contracting States:

AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE

Designated Extension States:

AL LT LV MK RO SI

(30) Priority: 13.01.1998 US 6248

(71) Applicant: BTM CORPORATION  
Marysville, Michigan 48040 (US)

(72) Inventors:

• Sawdon, Edwin G.  
St. Clair, Michigan 48079 (US)

• Petit, Brian D.  
Algonac, Michigan 48001 (US)

(74) Representative:

Price, Nigel John King  
J.A. KEMP & CO.  
14 South Square  
Gray's Inn  
London WC1R 5LX (GB)

### (54) End arm manipulator

(57) An end arm manipulator includes a base, an arm pivotably mounted to the base and a workpiece interfacing member coupled to the arm. In another aspect of the present invention, multiple arms are coupled to the base and are movable independent of each

other. In still another aspect of the present invention, generally spherical balls are adjustably mounted between a clamping member and a cavity of the base.




Fig. 2

EP 0 930 136 A2

BEST AVAILABLE COPY

## Description

[0001] This invention relates generally to workpiece interfacing apparatuses and more specifically to an end arm manipulator for retaining workpiece interfacing tools.

[0002] It is common to employ fluid powered grippers for engaging sheet metal workpieces. Such grippers are often movably mounted to a robotic or stationary support. Examples of such mounting arrangements are disclosed in the following U.S. Patent Nos.: 5,647,625 entitled "Gripper" which issued to Sawdon on July 15, 1997; 5,383,738 entitled "Ball Jointed Links" which issued to Herbermann on January 24, 1995; and 5,071,309 entitled "Mounting Arrangement for a Multi-Function Arm" which issued to Herbermann on December 10, 1991.

[0003] Another traditional device is constructed of multiple, extruded metal rails bolted to a generally square shaped frame. The frame is centrally attached to a moving robotic arm. Hoses extend from the hollow, box section rails which are used as air manifolds. Pneumatically powered grippers are adjustably mounted to various points on the rails. However, these traditional devices are custom fabricated for each particular job, are costly to produce and labor intensive to set up. These traditional devices require excessive amounts of actuating fluid due to the indirect right angle mounting of components and due to the use of rails as manifolds. Such conventional units are also relatively heavy and inefficiently packaged thereby causing accurate repeatability concerns, and a circuitous routing of electrical and pneumatic lines which are prone to snagging on adjacent equipment or the workpiece.

[0004] In accordance with the present invention, the preferred embodiment of an end arm manipulator includes a base, an arm pivotably mounted to the base and a workpiece interfacing member coupled to the arm. In another aspect of the present invention, multiple arms are coupled to the base and are movable independent of each other. In still another aspect of the present invention, generally spherical balls are adjustably mounted between a clamping member and a cavity of the base. The arms are telescopically extendable in a further aspect of the present invention. Yet another aspect of the present invention provides a fluid powered gripping tool or locating tool mounted on either an end or intermediate portion of an arm. Another aspect of the present invention provides a fluid manifold function as an integral part of the base.

[0005] The end arm manipulator of the present invention is advantageous over conventional constructions in that the present invention is quickly and easily adjusted for different workpiece set ups utilizing single or multiple arms in standardized packages. This eliminates the cost of individual fabrications and is reusable for other jobs. The present invention is also much more rigid than traditional devices since the present invention manipu-

lator's arms directly extend between a compact base and the workpiece, as compared to the traditional right angle geometry. The straight geometry construction of the present invention is also more easily packaged in a small work space while further shortening fluid lines and electrical lines. Moreover, the straight or direct geometry construction reduces the volume of fluid consumed compared to the conventional right angle and box framed structure. The majority of the electrical and fluid lines are also advantageously protectively contained within the arms. Additional advantages and features of the present invention will become apparent from the following description and appended claims, taken in conjunction with the accompanying drawings, which are now briefly described:

Figure 1 is a perspective view showing the preferred embodiment of an end arm manipulator of the present invention gripping a workpiece;

Figure 2 is a side elevational view showing the preferred embodiment end arm manipulator in multiple positions and with multiple other preferred workpiece interfacing tools;

Figure 3 is an enlarged and fragmentary side elevational view showing a base, clamp rings, balls and arms of the preferred embodiment end arm manipulator;

Figure 4 is a fragmentary bottom elevational view showing the base, clamp rings, balls and arms employed in the preferred embodiment end arm manipulator;

Figure 5 is an enlarged cross sectional view, taken along line 5-5 of Figure 4, showing the base, a clamp ring and a ball employed in the preferred embodiment end arm manipulator; and

Figure 6 is a fragmentary and exploded perspective view showing the clamp rings, balls, arms and base employed in the preferred embodiment end arm manipulator;

Figure 7 is an enlarged cross sectional view, taken along line 7-7 of Figure 4, showing the base employed in the preferred embodiment end arm manipulator;

Figure 8 is an enlarged and fragmentary side elevational view showing an arm, tube clamp and tool mount employed in the preferred embodiment end arm manipulator;

Figure 9 is an exploded perspective view showing the tool mount and a side elevational view showing a workpiece interfacing tool employed in the preferred embodiment end arm manipulator; and

Figure 10 is an enlarged side elevational view showing the workpiece interfacing tool, a tool mount and the arm employed in the preferred embodiment end arm manipulator.

[0006] Referring to Figures 1 and 2, the preferred embodiment of an end arm effector or manipulator 21 is

used to retain or transport a workpiece 23, such as a stamped steel, body side frame of an automotive vehicle, within a manufacturing plant. A robotic arm 25 is centrally bolted to end arm manipulator 21 for moving the manipulator and selectively engaged workpiece to various positions in the factory. Alternately, end arm manipulator 21 can be mounted to a manually moved support or stationary structure mounted to the factory floor.

**[0007]** End arm manipulator 21 includes an aluminum base 31, four aluminum clamp rings 33, four predominantly spherical balls 35, four telescoping arms 37 and workpiece interfacing tools as well as their associated mounts. Additional preferred arms 37', workpiece interfacing tools and their associated mounts are shown in Figure 2. Exemplary preferred tool configurations include grippers 41, 43, 45, 47, 49, 51, 53 and 55, which each include a circular cylindrically shaped body 71 (see Figure 9), an internally disposed pneumatic driven piston 73 and at least one moving jaw 75 for gripping the workpiece. Grippers 41-53 employ one or more pivoting jaws of the type known as the BTM PG-45 style flange gripper, double opening gripper or fixed gripper. Gripper 55 is of a parallel or box jaw type gripper known as the BTM SSLG style gripper. Other preferred workpiece interfacing tools include an electromagnetic coil proximity part-present sensor 77, a steel locator pin 79 and a vacuum cup 81.

**[0008]** The construction of base 31, clamp rings 33 and balls 35 can best be observed in Figures 3-6. Each clamp ring 33 is a C-shaped member having a side opening 101 and a top opening 103 through which arm 37 and a portion of ball 35 extend, respectively. Each clamp ring 33 further has an internal partially spherical cavity 105 for receiving the respective ball 35. Each corner of base 31 also has a partially spherical cavity 107 for receiving a corresponding ball 35. Bolts 109 are employed to loosely secure each clamp ring 33 to base 31, whereupon the corresponding ball trapped therebetween is pivotally adjusted to a desired orientation. After such a desired set up orientation is achieved, bolts 109 are tightened so as to secure and maintain the respective ball 35 and arm 37 in the final setup position. It should be appreciated, however, that each clamp ring 33 can be unbolted from base and rotated to many different rotational positions such that side opening 101 of each clamp ring 33 can be differently angled relative to base 31. If necessary, a dowel or screw can be inserted into aperture 121 in each clamp ring 33 for supplementally securing the corresponding ball 35 in its ultimately desired position.

**[0009]** A NEMA box 123 is fastened to the bottom of base 31 for containing electrical line or wire connections and controllers. Furthermore, the robotic arm is bolted to a central area 125 of base 31.

**[0010]** A manifold portion 141 of base 31 can be seen in Figures 4 and 7. Manifold portion 141 is integral with base 31 and includes a pair of longitudinally elongated

bore 143 and multiple transversely extending passageways 145 intersecting each bore 143. Bores 143 and passageways 145 are all drilled into base 31 although alternately, they may be integrally cast. It may be desired to thread the open ends of bores 143 and passageways to accept standard fittings. The main pneumatic fluid lines or hoses are coupled to the open ends of bores 143 while the individual tool pneumatic lines or hoses are connected to the open ends of respective passageways 145. Thus, manifold portion 141 of the present invention acts as a very compact, centralized and integral fluid receiving and distributing device.

**[0011]** Referring now to Figures 3, 6 and 10, each arm 37 is hollow and MIG welded to a corresponding ball 35 aligned with a first hole 201 in ball 35. Ball 35 is made as two separate and generally semi-spherical spun halves that are TIG welded together at TIG weld 203. Arms 37 and balls 35 are both made of steel. For each workpiece interfacing tool 47, two pneumatic lines 205 are routed from manifold portion 141, up through a lower hole 207 in base 31 and through a second downwardly facing hole 209 in ball 35. Pneumatic lines 205 are then routed in arm 37 and are allowed to exit through a laterally extending aperture 211. These pneumatic lines are then coupled to each fluid powered tool 47 for automatically and remotely activating the tool to grip or disengage workpiece 23. One or more electrical lines 231 are routed from box 123, up through hole 207, hole 209 and then in arm 37. Electrical lines 231 also exit arm 37 through aperture 211 and are then connected to a Turck switching or position sensing unit 233 mounted to tool 47.

**[0012]** Figure 8 illustrates the telescopic nature of arm 37. Arm 37 includes a proximal arm section 401 and a distal arm section 403. Distal arm section 403 has a slightly smaller outside diameter as compared to the inside diameter of proximal arm section 401. Thus, distal arm section 403 can be longitudinally slid into and out of proximal arm section 401 depending upon the desired set up length. Furthermore, distal arm section 403 can be rotated relative to proximal arm section 401 depending again upon the desired set up positioning; 360° distal arm section rotational movement is allowed. A tube clamp 405 engages the outside surface of proximal arm section 401 and serves to maintain the desired set up position of distal arm section 403 relative to proximal arm section 401 by tightening of screws 407. Four inwardly extending tabs of tube clamp 405 serve to slightly compress and crush the adjacent area of proximal arm section 401 thereby frictionally engaging a roughened outside diameter surface of distal arm section 403. If necessary, a dowel pin 409 or screw can additionally secure the arm sections relative to each other. Figure 8 also shows an intermediate arm positioning of a tool mount 411 along a generally middle or intermediate portion of arm 37.

**[0013]** An exemplary tool mount 451 is shown in Figures 9 and 10. Mount 451 includes a ball and socket

joint defined by a mount 453, a grooved first ball 455, a swivel rod 457, a mount ring 459, a mount plug 461 and a second grooved ball 463. Second ball 463 is integrally machined as part of rod 457. Mount plug 461 is fastened to a distal end of arm 37. Bolts 471 serve to secure mount ring 459 to mount plug 461 thereby compressing and maintaining second ball 463 in its finally adjusted pivotal orientation. Similarly, bolts 473 are secured to maintain mount 453 in its final desired set up position relative to the previously pivoted first ball 455 while also maintaining mount 453 in its desired angular and linear relationship relative to tool 47. These mount parts are machined from aluminum or steel with various oxide or hard coatings.

[0014] While the preferred embodiment of the end arm manipulator has been disclosed, it will be appreciated that various other embodiments may be employed without departing from the present invention. For example, the distal end ball and socket tool mounting arrangement can be employed independently of the rest of the invention. Furthermore, any number of ball, arm and clamp ring combinations can be employed with a single base; for example, it is envisioned that two, four and six arm to base combinations would be desirable for many factory applications. Moreover, hydraulic fluid, pneumatic fluid or electrically powered tools of any variety can be mounted to the present invention construction. For example, welding guns or riveting machines can be used. Various materials and fasteners have been disclosed in an exemplary fashion, however, other materials and fasteners may of course be employed. It is intended by the following claims to cover these and any other departures from the disclosed embodiments which fall within the true spirit of this invention.

## Claims

1. An end arm manipulator comprising:
  - a base;
  - a first arm pivotably mounted directly on said base;
  - a first workpiece interfacing member coupled to said first arm;
  - a second arm pivotably mounted on said base, said first and second arms being pivotable independently of each other; and
  - a second workpiece interfacing member coupled to said second arm.
2. The manipulator of Claim 1 wherein said first workpiece interfacing member is movably coupled to said first arm and is movable in at least two directions relative to said first arm.
3. The manipulator of Claim 2 further comprising at least one ball and socket joint coupling said first workpiece interface member to said first arm.
4. The manipulator of Claim 3 wherein said at least one ball and socket joint couples said workpiece interface member to a distal end of said first arm.
5. The manipulator of Claim 3 wherein said at least one ball and socket joint couples said first workpiece interface member to an intermediate portion of said first arm.
6. The manipulator of any one of the preceding claims further comprising a substantially spherical ball mounted to a proximal end of said first arm adjacent to said base.
7. The manipulator of claim 6 further comprising a clamp ring mounted to said base for securing said substantially spherical ball to said base in a desired one of a plurality of angular positions.
8. The manipulator of claim 7 further comprising a cavity in said base and a cavity in said clamp ring having shapes substantially conforming to the adjacent portions of said substantially spherical ball, said clamp ring being adjustably secured to said base in a desired one of a plurality of positions, said first arm extending through an opening in said clamp ring.
9. The manipulator of any one of the preceding claims further comprising:
  - an extension securing mechanism; and
  - a first section of said first arm telescopically extendable from a second section of said first arm;
  - said extension securing mechanism selectively maintaining said sections of said first arm relative to each other in a desired extension position.
10. The manipulator of any one of the preceding claims wherein said first and second arms have a circular-cylindrical shape and are substantially hollow.
11. The manipulator of claim 10 further comprising a fluid distributing manifold disposed in said base for supplying fluid through the interior of at least one of said arms.
12. The manipulator of any one of the preceding claims wherein said first workpiece interfacing member is a workpiece engaging gripper.
13. The manipulator of claim 12 wherein said gripper includes:
  - a body;
  - a pair of gripping jaws, at least one of jaws

being movable relative to said body; and  
a fluid actuated piston located in said body for  
opening and closing said at least one of said  
jaws.

5

14. The manipulator of any one of claims 1 to 11  
wherein said workpiece interfacing member is a  
locator pin, or a vacuum cup, or a workpiece sen-  
sor.

10

15. The manipulator of any one of the preceding claims  
further comprising a robotic member mounted to  
and moving said base.

16. The manipulator of any of claims 1 to 10 or 12 to 15  
further comprising a flexible line extending from  
said base to said first workpiece interfacing mem-  
ber through an interior of said arm.

15

17. The manipulator of any one of the preceding claims  
further comprising at least third and fourth arms  
pivotally mounted to said base, at least said first  
and second arms radially extending directly  
between said base and said respective first and  
second workpiece interfacing members.

20

25

30

35

40

45

50

55




Fig. 1





Fig-2








Fig-4




Fig-5




Fig-7




Fig-6





Fig-8






Fig-10

(19)



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11)

**EP 0 930 136 A3**

(12)

## EUROPEAN PATENT APPLICATION

(88) Date of publication A3:  
**12.01.2000 Bulletin 2000/02**

(51) Int. Cl.<sup>7</sup>: **B25J 18/00, B25J 15/00**

(43) Date of publication A2:  
**21.07.1999 Bulletin 1999/29**

(21) Application number: **98309247.9**

(22) Date of filing: **11.11.1998**

(84) Designated Contracting States:  
**AT BE CH CY DE DK ES FI FR GB GR IE IT LI LU  
MC NL PT SE**  
Designated Extension States:  
**AL LT LV MK RO SI**

(72) Inventors:  
• Sawdon, Edwin G.  
St. Clair, Michigan 48079 (US)  
• Petit, Brian D.  
Algonac, Michigan 48001 (US)

(30) Priority: **13.01.1998 US 6248**


(71) Applicant: **BTM CORPORATION**  
Marysville, Michigan 48040 (US)

(74) Representative:  
**Price, Nigel John King**  
**J.A. KEMP & CO.**  
14 South Square  
Gray's Inn  
London WC1R 5LX (GB)

### (54) End arm manipulator

(57) An end arm manipulator includes a base, an arm pivotably mounted to the base and a workpiece interfacing member coupled to the arm. In another aspect of the present invention, multiple arms are coupled to the base and are movable independent of each

other. In still another aspect of the present invention, generally spherical balls are adjustably mounted between a clamping member and a cavity of the base.



**Fig. 2**



European Patent  
Office

# EUROPEAN SEARCH REPORT

Application Number  
EP 98 30 9247

DOCUMENTS CONSIDERED TO BE RELEVANT			
Category	Citation of document with indication, where appropriate, of relevant passages	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int.Cl.6)
X	US 4 898 490 A (HERBERMANN ALFRED F ET AL) 6 February 1990 (1990-02-06) * figure 4 *	1-4, 6, 10, 12	B25J18/00 B25J15/00
Y	* column 4, line 42 - column 5 *	6-9, 13, 16, 17	
Y	FR 2 460 757 A (BLANLEUIL JEAN) 30 January 1981 (1981-01-30) * column 1, line 14-18; claim 1; figure 1 *	6-8	
Y	US 5 322 334 A (HAMMER MORDECHAI) 21 June 1994 (1994-06-21) * column 5, line 68 - column 6, line 14; figure 2 *	9	
Y	DE 32 44 211 A (ERNO RAUMFAHRTTECHNIK GMBH) 30 May 1984 (1984-05-30) * abstract; claim 1; figure 1 *	17	
Y	US 4 648 782 A (KRAFT BRETT W) 10 March 1987 (1987-03-10) * column 12, line 26-41 - column 4, line 11-16; figures 1, 30 *	13, 16	TECHNICAL FIELDS SEARCHED (Int.Cl.6) B25J
A	* column 3, line 53, 54 *	11	
X	US 4 922 782 A (KAWAI SEIJI) 8 May 1990 (1990-05-08) * column 2, line 56-62; figures 1, 2 *	1-4, 12, 15	
The present search report has been drawn up for all claims			
Place of search THE HAGUE		Date of completion of the search 19 November 1999	Examiner Lumineau, S
<p>CATEGORY OF CITED DOCUMENTS</p> <p>X : particularly relevant if taken alone Y : particularly relevant if combined with another document of the same category A : technological background O : non-written disclosure P : intermediate document</p> <p>T : theory or principle underlying the invention E : earlier patent document, but published on, or after the filing date D : document cited in the application L : document cited for other reasons &amp; : member of the same patent family, corresponding document</p>			

**ANNEX TO THE EUROPEAN SEARCH REPORT  
ON EUROPEAN PATENT APPLICATION NO.**

EP 98 30 9247

This annex lists the patent family members relating to the patent documents cited in the above-mentioned European search report. The members are as contained in the European Patent Office EDP file on  
The European Patent Office is in no way liable for these particulars which are merely given for the purpose of information.

19-11-1999

Patent document cited in search report		Publication date	Patent family member(s)		Publication date
US 4898490	A	06-02-1990	NONE		
FR 2460757	A	30-01-1981	NONE		
US 5322334	A	21-06-1994	US	5881601 A	16-03-1999
			US	5324086 A	28-06-1994
			AU	684467 B	18-12-1997
			AU	4671993 A	31-01-1994
			BG	99346 A	29-09-1995
			BR	9306734 A	08-12-1998
			CA	2139659 A	20-01-1994
			CZ	9500087 A	13-03-1996
			EP	0650405 A	03-05-1995
			FI	950143 A	10-03-1995
			HU	75562 A	28-05-1997
			JP	8500776 T	30-01-1996
			NO	950120 A	23-02-1995
			NZ	254563 A	23-12-1998
			PL	307161 A	02-05-1995
			SK	5195 A	06-03-1996
			WO	9401254 A	20-01-1994
DE 3244211	A	30-05-1984	NONE		
US 4648782	A	10-03-1987	NONE		
US 4922782	A	08-05-1990	JP	62068293 A	28-03-1987
			EP	0218139 A	15-04-1987



**This Page is Inserted by IFW Indexing and Scanning  
Operations and is not part of the Official Record**

**BEST AVAILABLE IMAGES**

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images include but are not limited to the items checked:

- ☐ BLACK BORDERS
- ☐ IMAGE CUT OFF AT TOP, BOTTOM OR SIDES
- ☒ FADED TEXT OR DRAWING
- ☐ BLURRED OR ILLEGIBLE TEXT OR DRAWING
- ☐ SKEWED/SLANTED IMAGES
- ☐ COLOR OR BLACK AND WHITE PHOTOGRAPHS
- ☐ GRAY SCALE DOCUMENTS
- ☒ LINES OR MARKS ON ORIGINAL DOCUMENT
- ☐ REFERENCE(S) OR EXHIBIT(S) SUBMITTED ARE POOR QUALITY
- ☐ OTHER: \_\_\_\_\_

**IMAGES ARE BEST AVAILABLE COPY.**

**As rescanning these documents will not correct the image problems checked, please do not report these problems to the IFW Image Problem Mailbox.**